

### 4x4 Dante™ Converter



Ref.	CV441D
Input Connectors	4 x detachable euroblock input
Output Connectors	4 x detachable euroblock output
Dante™ ports	2 RJ45 (primary and secondary)
RS232 port	1 detachable connector
Frequency response	20 Hz - 20 kHz (+/- 0.2 dB)
Power supply	100 - 240 V, 50/60 Hz
Power consumption	7.5 W
Dimensions (H x W x D)	45 x 215 x 145
Weight	1.38 kg (excluding racking brackets)

Input characteristics:	
Impedance	> 11 kohms
Gains	
- Line	0 dB / - 10 dB
- Micro	0 dB / 5 dB / 10 dB / 15 dB / 25 dB / 35 dB
Maximum level	
- Line	+12 dBu (+21.5 dBu with pad -10 dB)
- Micro	+12 dBu (gain 0 dB) / + 6.5 dBu (gain +5 dB) / +1dBu (gain +10 dB) / -4 dBu (gain +15 dB) / -13 dBu (gain +25 dB) / -24 dBu (gain +35 dB)
Signal to noise ratio (SNR)	> 106 dBA (@ 1 kHz +12 dBu)
THD	< 0.012% (@ 1 kHz +12 dBu)
Frequency response	20 Hz - 20 kHz (+/- 0.2 dB)

Output characteristics:	
Impedance	< 100 ohms
Maximum level	+12 dBu
Signal to noise ratio (SNR)	>106dBA (@1 kHz +12dBu)
THD	< 0,012% (@ 1 kHz +12 dBu)
Frequency response	20 Hz - 20 kHz (+/- 0,2 dB)

